

Slot Sub Reliable high-powered sound



Slot Sub

The Slot Sub features a newly designed amplifier delivering efficient and reliable high-powered sound. The front firing port design allows for maximum air flow and helps reduce port noise, while allowing unprecedented deep bass extension. Includes advanced circuitry to eliminate the potential for grounding noise.

The design boasts a premium two tone finish with beveled shape and a premium satin black paint. Front mounted slot port allows for cabinetry or flush wall mounting.





Slot Sub

Reliable high-powered sound





Enclosure Design: Driver:

Power: Frequency Range, LP: Frequency Range, LFE: Sensitivity: Crossover:

> Inputs: **Cabinet Dimensions:**

> > **Certifications:** Finish:

> > > Family:

SS-8

Front firing, slot port 8" coated cellulose composite 100 watt internal amplifier 33 - 190 Hz (+/-3 dB)

33 - 190 Hz (+/-3 dB) 130 mV @ 100W

40-200 Hz continuously variable low pass

Line level RCA, speaker level LFE 14.5" (368mm) high (including feet) 12" (304mm) wide

14" (357mm) deep (including grill and amp) CE, RCM, TUV, FCC

Black, matte paint, textured vinyl

UNIVERSAL

SS-10

Front firing, slot port

10" coated cellulose composite

150 watt internal amplifier

31 - 150 Hz (+/-3 dB) 31 - 150 Hz (+/-3 dB)

130 mV @ 150W

40-200 Hz continuously variable low pass

Line level RCA, speaker level LFE 16" (407mm) high (including feet)

13.4" (340mm) wide 16" (405mm) deep (including grill and amp) CE, RCM, TUV, FCC

Black, matte paint, textured vinyl

UNIVERSAL

SS-12

Front firing, slot port 12" coated cellulose composite 250 watt internal amplifier

25 - 140 Hz (+/-3 dB) 25 - 140 Hz (+/-3 dB)

151 mV @ 250W

40-200 Hz continuously variable low pass

Line level RCA, speaker level LFE 18.5" (470mm) high (including feet)

15" (380mm) wide

17" (447mm) deep (including grill and amp) CE, RCM, TUV, FCC

Black, matte paint, textured vinyl



