

PRODUCT SELECTION GUIDE

Product / Feature	Security Operations / MSSPs		Network Operations / MSPs						
	CyberScope ¹	LinkSprinter	Test Accessory	LinkRunner AT 3000	LinkRunner AT 4000	LinkRunner 10G	EtherScope nXG	AirCheck G3	AirMagnet Survey PRO
Ethernet Copper	10/100 Mbps & 1/2.5/5/10 Gbps	10/100/1000 Mbps	10/100/1000 Mbps (detects Multi-Gig and 10 Gbps)	10/100 Mbps & 1/2.5/5/10 Gbps					
Ethernet Fiber	1/10 Gbps			1 Gbps		1/10 Gbps			
PoE Test (up to 90W at PSE, 71.3W at PD)	•	Voltage only		•	•	•	•		
Wiremap & Toner - Cable Open/Short/Length	•			•	•	•	•		
Default Gateway, DNS, IP	Unlimited Targets	1 IP Target	1 IP Target	Unlimited Targets					
Wi-Fi Test/Heatmaps 802.11 a/b/g/n/ac/ax, Bands (2.4, 5, 6 GHz)	•						•	•	•
Wi-Fi Connection & Roaming Test	•						•	•	•
Discover SSID, AP, & Clients	•						•	•	•
AirWISE® Intelligence	•						•	•	•
AP & Client Locate	•						•	•	AP Locate Only
RF Traffic Statistics	•						•	•	
AirMapper™ Site Survey ²	•						•	•	•
Bluetooth/BLE Site Survey	•						•	•	
Wi-Fi Spectrum Analysis ³	Optional NXT-2000						Optional NXT-2000		
Network Topology Mapping ²	•				•	•	•	•	
Network Discovery	•				•	•	•	•	
Packet Capture	•				•	•	•	•	
LANBERT™ Media Qualification ⁴	Up to 10 Gbps			Up to 1 Gbps		Up to 10 Gbps			
iPerf Performance Test	•		•	•	•	•	•	•	•
Line Rate Performance Test	10 Gbps					10 Gbps			
Remote View/Control ²	•			•	•	•	•	•	Windows Apps
Integration of Nmap into AutoTest & Network Discovery	•								
Standalone Nmap App / Custom Script Support	•								
Automated Discovery Monitoring	•								
Option to Disable Functionality*	•			•	•	•	•	•	

¹The full function CE version includes wired Ethernet and wireless (Wi-Fi and BT/BLE) capabilities. Wired only (XRF) and wireless only (AIR) versions are also available - specific capabilities depend on the version. Refer to the CyberScope online [Model Comparison](#) for details.

²Depending on each product's capabilities, Link-Live gated features can include AirMapper enhanced site survey visualizations, advanced Network Topology Mapping filters, and Remote View/Control; these features are available to customers with AllyCare support or a Link-Live Enabled Features subscription.

³NXT-2000 is not supported by AirCheck G3 or CyberScope Air testers manufactured before August 2024. Contact Customer Service at www.netally.com/contact-us/ for more information and available options.

⁴LANBERT and Performance tests require the use of two units, a controller and remote.

*Allows disabling of specific product capabilities for use in secure environments.