

The APC 2S-14 presents a 2.4GHz CPE product with superior performance and flexibility. This product is equipped with an extreme output power (up to 31 dBm) 802.11n radio that was created with a unique hardware design and coupled with a reliable, feature-rich operating system. This small device also has a robust, IP-65 compliant enclosure which is combined with a medium gain corner reflector, and emits EIRP up to 35 W. The APC 2S-14 is generally designed for CPE applications but can also act as an access point thus allowing point to point and point


to multipoint network applications.

The included, robust software engine allows the APC 2S-14 to work as bridge or as a router, provides a user-friendly Adobe Flex - based GUI with instant changes, includes useful installation tools (Site survey, Antenna alignment, Delayed reboot, Spectrum analyzer), and also is compatible with Wireless Network Management System for one of the most advanced management tools on the market.

Usage examples

PTMP

Deliberant APC 2S-14 is an ideal device for point-to-multiple point applications as a short to medium range client device.



PTP

APC 2S-14 is a great device for short to medium range point-to-point applications.



Product/ distance recommendation	PTMP mode	PTP mode	PTP mode (full capacity)
APC 2S-14	10 km/ 6.21 mi	30 km/ 18.64 mi	4 km/ 2.49 mi

Wireless

WLAN standard	IEEE 802.11 b/g/n
Radio mode	SiSo 1x1
Operating modes	Access point, Access point WDS, Client, Client WDS
Radio frequency band	2.4 GHz
Transmit power	Up to 31 dBm
Receive sensitivity	Varying between -94 and -70 dBm depending on modulation
Channel size	20, 40 MHz
Modulation schemes	802.11 g/n: OFDM (64-QAM, 16-QAM, QPSK, BPSK) 802.11 b: DSS (CCK, DQPSK, DBPSK)
Data rates	802.11 n: 120, 90, 60, 30 Mbps 802.11 g: 54, 48, 36, 24, 18, 12, 9, 6 Mbps 802.11 b: 11, 5.5, 2, 1 Mbps
Error correction	FEC, Selective ARQ, STBC
Duplexing scheme	Time division duplex

Receive sensitivity (dBm)	802.11N/iPoll	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
		-94	-91	-89	-86	-83	-78	-77	-75
802.11g	6 Mbps	9 Mbps	12 Mbps	18 Mbps	24 Mbps	36 Mbps	48 Mbps	54 Mbps	
	-95	-94	-92	-90	-88	-84	-80	-78	
802.11b	1 Mbps	2 Mbps	5.5 Mbps	11 Mbps	-	-	-	-	
	-95	-95	-95	-93	-	-	-	-	

Output power (dBm)	802.11N/iPoll	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
		30	30	30	30	28	28	28	26
802.11g	6 Mbps	9 Mbps	12 Mbps	18 Mbps	24 Mbps	36 Mbps	48 Mbps	54 Mbps	
	31	31	31	31	31	31	29	29	
802.11b	1 Mbps	2 Mbps	5.5 Mbps	11 Mbps	-	-	-	-	
	27	27	27	27	-	-	-	-	

Antenna

Type	Integrated directional or sector antenna
Gain	14 dBi (directional) or 10 dBi (sector)

Wired

Interface	10/100 Base-T, RJ45
Built-in surge protection	Yes

Networking

Operating modes	Bridge, Router
WAN	Static IP, DHCP client, PPPoE client
NAT	Routing w/ or w/o NAT
Static routing	Supported
DHCP	Client, Server, Relay
Port forwarding	Supported
VLAN	Supported for management and data

Security

Wireless security	WEP, WPA/WPA2 Personal, WPA/WPA2 Enterprise, WMM, WACL
User isolation	Supported

Software

General	Ability to define/limit frequency, channel width, EIRP, modulation All configurations are instant changes
Operating mode	Router, Bridge
Wireless operating modes	AP, Station, AP WDS, Station WDS, Virtual radios (VSSID)
Wireless security	WPA/WPA2 Personal, WPA/WPA2 Enterprise, WACL, User isolation
Wireless QoS	WMM
WAN protocols	Static IP, DHCP client, PPPoE client
Network	NAT, static routing, firewall, port forwarding, VLAN
Services	DHCP server, SNMP server, NTP client, Alerts, Remote syslog, Wireless and Ethernet statistics, bandwidth limiting
Management	HTTP(S) GUI, SSH CLI, SNMP read, WNMS, troubleshooting file, reset via ICMP
Tools	Site survey, Link test, Antenna alignment, Ping, Traceroute, Spectrum analyzer

Physical

Dimensions	Length 248 mm (9.76 "), width 211 mm (8.3 "), height 100 mm (3.9 ")
Weight	500 g (17.6 oz)
Power supply	12 - 24 V DC passive PoE
Power source	100 – 240 VAC via included adapter
Power consumption	4.5 W

Environmental

Operating temperature	-20°C (-4 F) ~ +55°C (+131 F)
Humidity	0 ~ 90 % (non-condensing)


Management

System configuration	User-friendly web GUI, Command line via SSH, centralized Wireless Network Management System, reset to defaults via special ICMP packet
System monitoring	SNMP v1/2c/3 server, Syslogs, system alerts via e-mail and SNMP trap
Certification	FCC/CE (*pending)


Regulatory

Safety	RoHS compliant
--------	----------------

Antenna specifications



Frequency range	2.4 - 2.5 GHz
Gain (reflector/ no reflector)	14 dBi/ 10 dBi
Polarization	Dual linear
Cros-pol Isolation	40 dBi minimum
Max VSWR	1.8:1
Beamwidth with reflector	20 deg
Beamwidth without reflector	54 deg
Elevation Beamwidth	50 deg



*Note: This product has not been authorized by the rules of the Federal Communications Commission. This product may not be sold or leased, or offered for sale or lease, in the United States, until authorization has been obtained.



www.deliberant.com

Copyright © 2011 Deliberant LLC. All rights reserved. Deliberant, the Deliberant logo, are trademarks of Deliberant LLC. All other company and product names may be trademarks of their respective companies. While every effort is made to ensure the information given is accurate, Deliberant does not accept liability for any errors or mistakes which may arise. Specifications and other information in this document may be subject to change without notice.



To learn more about Deliberant products, visit www.deliberant.com.